

Power and Current ratings

Model	Frame size	Number of input phases	Supply volts +/-10%	kW rating	HP rating	100% Output current A	150% Output current A
SE11200025	1	1	200-240	0.25	0.33	1.5	2.3
SE11200037	1	1	200-240	0.37	0.5	2.3	3.5
SE11200055	1	1	200-240	0.55	0.75	3.1	4.7
SE11200075	1	1	200-240	0.75	1	4.3	6.5
SE2D200075	2	1 or 3	200-240	0.75	1	4.3	6.5
SE2D200110	2	1 or 3	200-240	1.1	1.5	5.8	8.7
SE2D200150	2	1 or 3	200-240	1.5	2	7.5	11.3
SE2D200220	2	1 or 3	200-240	2.2	3	10.6	15.9
SE23200400	2	3	200-240	4	5	17	25.5
SE33200550	3	3	200-240	5.5	7.5	25	37.5
SE33200750	3	3	200-240	7.5	10	28.5	42.8
SE23400075	2	3	380-480	0.75	1	2.1	3.2
SE23400110	2	3	380-480	1.1	1.5	3	4.5
SE23400150	2	3	380-480	1.5	2	4.2	6.3
SE23400220	2	3	380-480	2.2	3	5.8	8.7
SE23400300	2	3	380-480	3	4	7.6	11.4
SE23400400	2	3	380-480	4	5	9.5	14.3
SE33400550	3	3	380-480	5.5	7.5	13	19.5
SE33400750	3	3	380-480	7.5	10	16.5	24.8
SE43401100	4	3	380-480	11	15	24.5	36.8
SE43401500	4	3	380-480	15	20	30.5	45.8