

No. de Depósito	Descripción			
	Tipo	I nominal motor (A)	Potencia del motor (HP) ⁹⁾	
			220 V	440 V
100045313	3RW4422-1BC34	29	7.5	15
100036157	3RW4423-1BC34	36	10	20
100018175	3RW4424-1BC34	47	15	25
100018177	3RW4425-1BC34	57	18	30
100036159	3RW4426-1BC34	77	20	50
100045632	3RW4427-1BC34	93	25	60
100044954	3RW4434-6BC34	113	30	75
100035882	3RW4435-6BC34	134	40	90
100035885	3RW4436-6BC34	162	50	100
100036147	3RW4443-6BC34	203	60	125
100036149	3RW4444-6BC34	250	75	150
100036153	3RW4445-6BC34	313	100	200
100026315	3RW4446-6BC34	356	125	250
100018169	3RW4447-6BC34	432	150	300
100018202 ²⁾	3RW4453-6BC34	551	200	400
100018203 ²⁾	3RW4454-6BC34	615	230	450
100045323 ²⁾	3RW4455-6BC34	693	250	500
100075042 ²⁾	3RW4456-6BC34	780	280	600
100045506 ²⁾	3RW4457-6BC34	880	300	700
100045668 ²⁾	3RW4458-6BC34	970	-	750
100075076 ²⁾	3RW4465-6BC34	1076	400	800
100075073 ²⁾	3RW4466-6BC34	1214	450	900
	Conexión dentro de la delta para motores de al menos 6 terminales. Aplicaciones hasta 230 V AC.			
100045313	3RW4422-1BC34	50	15	
100036157	3RW4423-1BC34	62	20	
100018175	3RW4424-1BC34	81	25	
100018177	3RW4425-1BC34	99	30	
100036159	3RW4426-1BC34	133	40	
100045632	3RW4427-1BC34	161	50	
100044954	3RW4434-6BC34	196	60	
100035882	3RW4435-6BC34	232	75	
100035885	3RW4436-6BC34	281	100	
100036147	3RW4443-6BC34	352	125	
100036149	3RW4444-6BC34	433	150	
100036153	3RW4445-6BC34	542	200	
100026315	3RW4446-6BC34	617	230	
100018169	3RW4447-6BC34	748	250	
100018202 ²⁾	3RW4453-6BC34	954	350	
100018203 ²⁾	3RW4454-6BC34	1065	400	
100045323 ²⁾	3RW4455-6BC34	1200	450	
100075042 ²⁾	3RW4456-6BC34	1351	500	
100045506 ²⁾	3RW4457-6BC34	1524	600	
100045668 ²⁾	3RW4458-6BC34	1864	750	
100075076 ²⁾	3RW4465-6BC34	2103	850	